





RoHS
Compliant
2002/95/EC


REV.	ECN.	NO.	APPD.

DIMENSIONS




P.C.B MOUNTING PATTERN DIMENSION


The following soldering patterns are recommended for reflow soldering



CIRCUIT DIAGRAM



PRODUCT IMAGE



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.15 ± 0.1mm
Operating Force	160±50gf
Operating Life(cycles)	100,000

.X ±0.2	X. ±2'
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.	

UNITS	mm	雅安科技有限公司 ACCURATE INNOTECH INC.			
MAT'L	SEE NOTE	PART NO.: AT-1100AACP SERIES			
FINISH	SEE NOTE	TITLE: TACT SWITCH		DWG NO.: ASI-1100AACP	
Q'TY		DR: Ricky 2014/03/24		CHKD: Ricky 2014/03/24	
		APPD:		SCALE	SHEET
				1:1	1/1
				REV.	CUSTOMER
				A	DRAWING