





RoHS
Compliant
2002/95/EC



REV.	ECN.	NO.	APPD.

DIMENSIONS




P.C.B MOUNTING PATTERN DIMENSION


The following soldering patterns are recommended for reflow soldering



CIRCUIT DIAGRAM



PRODUCT IMAGE



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.2 ± 0.1mm
Operating Force	250±50gf
Operating Life(cycles)	50,000

					.X ±0.3	X. ±2'	UNITS mm	雅安科技有限公司 ACCURATE INNOTECH INC.				
							MAT'L	TITLE:		PART NO.:		
							SEE NOTE	TACT SWITCH		AT-1186AU1 SERIES		
							FINISH	DR:		DWG NO.:		
							SEE NOTE	Ricky 2026/08/17		ASI-1186AU1		
							Q'TY	CHKD:		REV.		
								Ricky 2026/08/17		CUSTOMER		
								APPD:		DRAWING		

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

