







RoHS
Compliant
2002/95/EC


REV.	ECN.	NO.	APPD.

DIMENSIONS



P.C.B MOUNTING PATTERN DIMENSION
The following soldering patterns are recommended for reflow soldering

CIRCUIT DIAGRAM



PRODUCT IMAGE



ELECTRO-MECHANICAL CHARACTERISTICS
Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.2 ± 0.1mm
Operating Force	250±50gf
Operating Life(cycles)	50,000

.X	±0.3	X.	±2'
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.			

UNITS	mm	雅安科技有限公司 ACCURATE INNOTECH INC.			
MAT'L					
SEE NOTE		TITLE:	TACT SWITCH	PART NO.:	AT-1186AU2 SERIES
FINISH		DR:	Ricky 2026/08/17	DWG NO.:	ASI-1186AU2
SEE NOTE		CHKD:	Ricky 2026/08/17	SCALE	1:1
Q'TY		APPD:		SHEET	1/1
				REV.	A
				CUSTOMER	DRAWING