






RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.


DIMENSIONS



CIRCUIT DIAGRAM





PRODUCT IMAGE



P.C.B MOUNTING PATTERN DIMENSION

The following soldering patterns are recommended for reflow soldering



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.2 ± 0.1mm
Operating Force	250±50gf
Operating Life(cycles)	50,000

.X	±0.3	X.	±2'
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.			

UNITS	mm	雅安科技有限公司 ACCURATE INNOTECH INC.			
MAT'L					
SEE NOTE		TITLE:	PART NO.:		
FINISH		TACT SWITCH	AT-1186BP2 SERIES		
SEE NOTE		DR: Ricky 2026/08/17	DWG NO.:		
Q'TY		CHKD: Ricky 2026/08/17	ASI-1186BP2		
		APPD:	SCALE	SHEET	REV.
			1:1	1/1	A
					CUSTOMER DRAWING