








RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.


DIMENSIONS



P.C.B MOUNTING PATTERN DIMENSION

The following soldering patterns are recommended for reflow soldering

CIRCUIT DIAGRAM



PRODUCT IMAGE



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.15 ± 0.1mm	
Operating Force	160±50gf	250±50gf
Operating Life(cycles)	50,000	

.X	±0.3	X.	±2'
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.			

UNITS	mm			
MAT'L				
SEE NOTE				
FINISH				
SEE NOTE				
Q'TY				

雅安科技有限公司 ACCURATE INNOTECH INC.			
TITLE: TACT SWITCH	PART NO.: AT-1186SAP1 SERIES		
DR: <i>Ricky</i> 2026/08/17	DWG NO.: ASI-1186SAP1		
CHKD: <i>Ricky</i> 2026/08/17	SCALE 1:1	SHEET 1/1	REV. A
APPD:	CUSTOMER DRAWING		