






RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



DIMENSIONS



CIRCUIT DIAGRAM



P.C.B MOUNTING PATTERN DIMENSION
The following soldering patterns are recommended for reflow soldering



ELECTRO-MECHANICAL CHARACTERISTICS
Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.2 ± 0.1mm
Operating Force	200±50gf
Operating Life(cycles)	50,000

E					.X ±0.3	X. ±2'	UNITS	雅安科技有限公司 ACCURATE INNOTECH INC.			
							mm				
							MAT'L	TITLE: TACT SWITCH			
							SEE NOTE				
							FINISH	PART NO.: AT-1192A SERIES			
							SEE NOTE				
							Q'TY	DWG NO.: ASI-1192A			
							THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.	CHKD: Ricky 2024/03/22			
								APPD: Ricky 2024/03/22			
								SCALE	SHEET	REV.	CUSTOMER
								1:1	1/1	A	DRAWING