





RoHS
Compliant
2002/95/EC



REV.	ECN.	NO.	APPD.

DIMENSIONS




P.C.B MOUNTING PATTERN DIMENSION


The following soldering patterns are recommended for reflow soldering



CIRCUIT DIAGRAM



PRODUCT IMAGE



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100m Ω Max.
Travel	0.3 $\pm$ 0.1mm
Operating Force	500 $\pm$ 100gf
Operating Life(cycles)	50,000

.X	± 0.2	X.	$\pm 2^{\circ}$
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.			

UNITS	mm
MAT'L	
SEE NOTE	
FINISH	
SEE NOTE	
Q'TY	

雅安科技有限公司
ACCURATE INNOTECH INC.

TITLE:	TACT SWITCH	PART NO.:	AT-1205 SERIES
DR:	Ricky 2026/08/15	DWG NO.:	ASI-1205
CHKD:	Ricky 2026/08/15	SCALE	1:1
APPD:		SHEET	1/1
		REV.	A
		CUSTOMER	DRAWING