










RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



NOTES:

1.ELECTRICAL:

- 1)VOLTAGE CURRENT RATING: 1AMP,30V AC;
- 2)INSULATION RESISTANCE: 100MΩ MIN;
- 3)CONTACT RESISTANCE: 30mΩ MAX;
- 4)WITHSTANDING VOLTAGE: 250V AC;
- 5)OPERATING TEMPERATURE:-30°C TO +85°C.

2.MECHANICAL:

- 1)MATING FORCE: 35N MAX.
- 2)UNMATING FORCE: 8N MIN.

3.DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

MUYM-051N-4BSU56

1:Au 1U*
6:Au 30U*

W:WHITE
B:BLACK

1:PBT
2:PA6T
3:PA9T
4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	.X	±0.30	.X*	±5*	UNITS	mm	雅安科技有限公司 ACCURATE INNOTECH INC.			
5					.X	±0.30	.X*	±5*	UNITS	mm	TITLE: MICRO USB BM 5P T=2.6 L=10.5 外露6.7 单排 前五后四			
4	LATCH	STAINLESS STEEL	2		.XX	±0.20	.XX*	±2*	MAT'L					
3	SHELL	STAINLESS STEEL	1	PLATED NICKEL	.XXX	±0.10			SEE NOTE		PART NO.: MUYM-05XN-4BSU56			
2	CONTACT	COPPER ALLOY	5	PLATED GOLD/TIN					FINISH					
1	HOUSING	LCP+30%GF	1	UL94V-0	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.					Q'TY	CHKD: Ricky 2025/05/09	DWG NO.: AII-SU56		
											APPD:			
											SCALE	SHEET	REV.	CUSTOMER DRAWING
											1:1	1/1	A	